

# BLACK JACK®

T R A I L E R   J A C K



USER MANUAL

## **Black Jack® Master** **1600kg 12V DC**

P/N: BJTJ-Master-1000, BJTJ-Master-1001

Please read and understand all instructions  
before use. Retain this manual for future reference.

[www.blackjacktrailerjacks.com.au](http://www.blackjacktrailerjacks.com.au)



## CONTENTS

|                                |    |
|--------------------------------|----|
| 1. Specifications              | 4  |
| 2. Introduction                | 4  |
| 3. Safety                      | 5  |
| 4. Hazard Definitions          | 5  |
| 5. Personal Precautions        | 6  |
| 6. Specific Safety Precautions | 6  |
| 7. Electrical Safety           | 7  |
| 8. Assembly & Installation     | 8  |
| 9. Operation                   | 9  |
| 10. Unhitching The Trailer     | 9  |
| 11. Hitching The Trailer       | 10 |
| 12. Manual Override            | 10 |
| 13. Care & Maintenance         | 11 |
| 14. Optional Folding Foot      | 12 |
| 15. Troubleshooting            | 14 |
| 16. Warranty & Parts           | 16 |
| 17. Intellectual Property      | 16 |
| 18. Compliance                 | 17 |

## 1. SPECIFICATIONS

|                       |                                                              |
|-----------------------|--------------------------------------------------------------|
| Maximum Load Capacity | 1600 kg                                                      |
| Stroke Length         | 450mm                                                        |
| Foot Plate            | Removable 133mm diameter foot plate or optional folding foot |
| Handle                | Manual crank override                                        |
| Tube Diameter         | 58mm outer Dimension                                         |
| Construction          | Steel tubes and plate and polypropylene cover                |
| Motor Type            | Sealed encapsulated brushless motor                          |
| Finish                | Powder coat tube, zinc plated inner and drop tubes           |
| Overall Dimensions    | H 835 x W 170 x D 130mm                                      |
| Voltage Rating        | 12V DC                                                       |
| Circuit Protection    | 30A Thermal Circuit Breaker, Safe Auto Stop                  |
| Current Rating        | Maximum 28A (Extended), 6A (Retracted)                       |
| IP Rating             | Minimum IP55                                                 |

## 2. INTRODUCTION

Congratulations on your new Black Jack!

The Black Jack Master Trailer Jack is rated to support up to 1600kg trailer tongue weight and with the patented Black Jack Clamp, it can be fitted to any trailer A-frame.

The Black Jack Master represents the latest technology in electric jacks, and features:

- Black Jack Safe Auto Stop
- Black Jack Folding Foot

The Black Jack features an LED light to illuminate the hitch area at night and a built-in levelling gauge. It also features a high quality cover to protect it against dirt, moisture and harsh conditions that exist behind a tow vehicle.

It comes with a choice of 2 feet: The traditional leg extension foot that can be adjusted, and the amazing new Black Jack folding foot. The choice is yours.

### 3. SAFETY

**WARNING! Read and understand all instructions before using this device. The operator must follow basic precautions to reduce the risk of personal injury and/or damage to the equipment.**

Keep this manual for safety warnings, precautions, operating or inspection and maintenance instructions.

### 4. HAZARD DEFINITIONS

Please familiarise yourself with the hazard notices found in this manual. A notice is an alert that there is a possibility of property damage, injury, or death if certain instructions are not followed.

#### **DANGER!**

This notice indicates an immediate and specific hazard that will result in severe personal injury or death if the proper precautions are not taken.

#### **WARNING!**

This notice indicates a specific hazard or unsafe practice that could result in severe personal injury or death if the proper precautions are not taken.

#### **CAUTION!**

This notice indicates a potentially hazardous situation that may result in minor or moderate injury if proper practices are not taken.

#### **NOTICE!**

This notice indicates that a specific hazard or unsafe practice will result in equipment or property damage, but not personal injury.

## 5. PERSONAL PRECAUTIONS

Control the device, personal movement, and the work environment to avoid personal injury or damage to device.

Do not operate any device when tired or under the influence of drugs, alcohol, or medications.

Avoid wearing clothes or jewelry that can become entangled with the moving parts of a device. Keep long hair covered or bound.

## 6. SPECIFIC SAFETY PRECAUTIONS

**WARNING! DO NOT let comfort or familiarity with product (gained from repeated use) replace strict adherence to the device safety rules. If you use this device unsafely or incorrectly, you can suffer serious personal injury.**

This device was designed for a specific function. Do not modify or alter this device or use it for an unintended purpose.

Do not attempt to lift more than the 1600 kg maximum lifting capacity of this jack.

Always place the jack on a hard, level surface capable of supporting the load. Allow enough clearance around the jack and the load for movement.

Never place any part of your body beneath the trailer that is supported by the jack. A jack failure or shifting of the trailer may cause it to collapse and cause a serious injury or death.

Keep your limbs and body away from any pinch or shearing points while using the jack. Failure to do so may result in a serious injury.

Inspect the jack before each use. DO NOT use if bent, broken, cracked or otherwise damaged, if any suspect parts are noticed or it has been subjected to a sudden or unexpected load (shock loading).

Ensure that all applicable pins, bolts, and nuts are firmly tightened before using.

Do not allow untrained persons to operate the jack. Secure the load, trailer, and vehicle by chocking all the wheels and applying the hand brake before using.

Do not place your hands between moving components.

Use only with accessories rated to handle the forces exerted by the device during operation. Other accessories may break and forcefully launch pieces.

Ensure that there are no obstructions under the load and that the area is clear before lowering it.

Ensure that the lock pin is properly inserted through the inner and outer tubes, and that there is no load on the trailer before using the manual drop leg extension.

Do not adjust the drop foot while there is a load on the Black Jack.

## 7. ELECTRICAL SAFETY

Disconnect device from power source before cleaning, servicing, changing parts/ accessories or when not in use

Protect yourself against electric shocks when working on electrical equipment. Avoid body contact with grounded surfaces. There is an increased chance of electrical shocks if your body is grounded.

Do not expose internals to rain or wet conditions. Water entering a power device will increase the risk of electric shock.

Do not alter any parts of the device or accessories. All parts and accessories are designed with built-in-safety features that may be compromised if altered.

Make certain the power source conforms to requirements of your equipment (see Specifications).

Do not operate this device if the leads are frayed or damaged as an electric shock or surge may occur, resulting in personal injury or property damage.

Inspect the leads for cracks, fraying or other faults in the insulation before each use. Discontinue use if the leads feel more than comfortably warm while operating the device.

Keep all connections dry and off the ground to reduce the risk of electric shock. Do not touch the leads with wet hands.

Keep the leads away from heat, oil, sharp edges or moving parts.

Install caps over the battery terminals to prevent accidental contact. Discharged batteries may still carry charges and cause electric shock upon contact.

## 8. ASSEMBLY & INSTALLATION

1. Attach and secure the trailer's coupler to the tow vehicle's hitch. Chock the wheels of the trailer and vehicle. Also apply the vehicle's parking brake.
2. Mount the Black Jack bracket to the chassis using the 4 M12 bolts and lock nuts. These bolts must be tightened to no more than 50Nm to prevent the bracket from warping.
3. Slide the Black Jack into the mounting bracket hole. Guide the foot plate into the jack's leg. Ensure the groove in the leg is aligned with the one on the foot plate. Do not insert the lock pin.
4. Position the jack to face your preferred operating position, either front, sideways or facing the rear.
5. The design of the vehicle may impair the use of the manual crank based on the jack's orientation.
6. Insert the three M10 bolts with M10 washers through the mounting plate and secure with the M10 lock nuts and washers. These M10 bolts should also be tightened to a maximum of 50Nm.
7. Tighten the bolts ensuring the whole unit is tightly secured to the A-Frame.
8. Connect the 50amp Andersen plug to an existing Black or Grey Andersen plug.
9. Connect the supplied wiring harness to the Black Jack and the other end of the wiring harness to the 12 volt Battery (model BJTJ-Master-1001).
10. Press the UP/DOWN switch to test that the connection is correct, and the jack is working. Also press the LIGHT ON/OFF Switch to confirm the light is working.
11. Push the foot plate up fully and insert the lock pin and retract the jack.
12. If installing the optional folding foot, please refer to the installation guide and warnings on page 13.



## 9. OPERATION

### 9.1 USING THE UP/DOWN SWITCH

The UP/DOWN switch is OFF in its natural position.

The Up/Down switch is wired relative to how you want the Caravan/Trailer to move.

If you want to raise the caravan, press the switch UP. This will extend the leg and raise the caravan. Hence, the "UP" function.

If you want to lower the caravan, press the switch DOWN. This will retract the leg and lower the caravan. Hence, the "DOWN" function.

Please Note: When the Black Jack is fully extended or fully retracted the Black Jack Safe Auto Stop system will automatically cut power to the motor.

### 9.2 USING THE ON/OFF LIGHT SWITCH

The ON\OFF switch is for the light only. It does NOT switch power on or off to the Black Jack. It turns the light on, and turns the light off.

## 10. UNHITCHING THE TRAILER

Chock the trailer's wheels to prevent rolling and apply the hand brake.

Press the UP/DOWN switch to the up position, to extend the jack's leg until the foot plate contacts the ground and raises the trailer off the hitch.

If the fully extended leg does not reach the ground. Retract the leg until you have enough room to extend the foot plate. Remove the lock pin and lower the adjustable foot plate until it touches the ground.

Move the towing vehicle away from the trailer's hitch receiver.

Level the trailer by pressing the UP/DOWN switch to raise or lower the jack. It is level once the bubble level is centered.

## 11. HITCHING THE TRAILER

Press the UP/DOWN switch upward to raise the trailer's hitch receiver above the level of the towing vehicle's hitch.

Align the towing vehicle's hitch with the trailer hitch receiver.

Press the UP/DOWN switch downward to lower the trailer hitch receiver onto the towing vehicle hitch. Secure the hitch receiver once seated.

Ensure the Jack is fully retracted before departing.

**WARNING! The hitch receiver must be properly aligned and seated before retracting the leg fully to prevent it from slipping off the hitch and causing an injury to yourself or bystanders.**

## 12. MANUAL OVERRIDE

A loss of power may require you to raise and lower the trailer using the manual operating handle.

Unscrew the manual handle cap that is under the bubble level on the top of the jack and set aside.

Insert the manual handle into the head of the jack so that it connects with the top of the worm drive.

Crank counter clockwise to extend the leg. Crank clockwise to retract the leg.

Follow the directions for hitching or unhitching the trailer.

Replace the manual handle cap when done and store the manual operating handle.

### 13. CARE & MAINTENANCE

Maintain the device with care. A Black Jack in good condition is efficient, easier to control and will have few problems. Inspect the device components periodically. Repair or replace damaged or worn components. Only use identical replacement parts when servicing.

Inspect and lubricate the device when required. Apply grease to the inner tube when extended and then retract to grease the inner and outer tube

NEVER use a penetrating oil to lubricate the device. Penetrating oil may act as a solvent that can break down the grease and cause the device to seize up.

The Black Jack's motor is sealed and maintenance-free.

## 14. OPTIONAL FOLDING FOOT

Your new Black Jack comes with a choice of two feet.

The silver steel foot is the traditional adjustable foot. You can manually adjust the height and it will tuck up under the chassis tightly.

The Black Jack folding foot will automatically drop from the horizontal position to the vertical position when the leg is extended saving time and without the need to manually adjust the foot. When retracting, the folding foot will automatically move from the vertical position to horizontal, again saving time.


The choice of feet to use is up to you and will be based on your individual set up and requirements.



## 14. OPTIONAL FOLDING FOOT

### Black Jack Folding Foot Installation.

The folding foot must be installed so that it is clear of any obstructions. The folding foot must be able to freely extend and retract to its full extension and full horizontal retraction.



If the foot encounters an obstruction, for example:

- a chassis rail
- brake cables,
- Bottom of the Black Jack Clamp

before it is fully retracted to a horizontal position then there is a risk of serious internal mechanical damage to the Black Jack. The damage is caused by the leverage pressure (up to 3,500kg) the folding foot can add if it encounters an obstruction. This type of damage is NOT covered under warranty as it is a user installation error.

When installing the folding foot, make sure the Black Jack orientation allows for full clearance of the folding foot. This may mean rotating the orientation of the Black Jack. If the folding foot cannot be installed so that it is clear of obstructions, then DO NOT USE IT. Install the silver adjustable foot instead.

## 15. TROUBLESHOOTING

Contact Titan RV for a solution if the device does not function properly or parts are missing. If you are unable to do so, get a qualified technician to service the device. Also, check the troubleshooting guide below:

| Problems                      | Possible Cause(s)               | Suggested Solution(s)                                                                                                                                                                                 |
|-------------------------------|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Motor is not operating        | No or Low Voltage               | Check battery and electrical connections. Power supplied must be at least 12.2V DC. If the battery is low, plug the Black Jack into an alternative 12 volt supply to provide power to the Black Jack. |
|                               | No Power from trailer connector | Check the trailer connector has power. Replace or repair the trailer connectors or wiring.                                                                                                            |
| Light Operates but not Motor  | Low Voltage                     | Check voltage inside Black Jack is minimum 12.2 volts.                                                                                                                                                |
|                               | UP/DOWN Switch is faulty        | Check power at middle positive terminal on switch when UP or DOWN is pressed. If no voltage is shown then the switch is faulty.                                                                       |
| Light and Motor not operating | Blown Fuse                      | Check fuse in the line to the power supply and replace with 30-40 amp fuse.                                                                                                                           |

## The 30-amp fuse keeps blowing

Normal operating range for a 300kg load is 8 amps retracting (DOWN) and up to 18 amps extending (UP). At a maximum weight of 1600kg, the Black Jack pulls 28 amps extending. So under normal operation the 30-amp fuse should not blow.

| Problems           | Possible Cause(s)                             | Suggested Solution(s)                                                                                                                                                                                                                            |
|--------------------|-----------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Fuse keeps blowing | Poor Ground/Earth will cause the fuse to blow | A bad Earth or poor connections. Check all connections between the battery and Jack are tight. Check the earth point is secure and any connecting circuits.                                                                                      |
|                    | Folding Foot Obstruction                      | If the folding foot is not clear to fully retract, the Safe Auto motor will not automatically stop the motor. This can cause the fuse to blow, and cause damage to the jack. Please see Section 16, page 12 of this manual for more information. |
|                    | Poor power supply                             | Most common cause is the wire gauge used between the battery and Black Jack is too small. A minimum of number 8 B&S (7.2MM) wire used over 5 meters. We recommend our Harness Part No. BJTJ-HAR                                                  |
|                    |                                               | Use a 40 amp fuse                                                                                                                                                                                                                                |

## 16. WARRANTY & PARTS

All replacement parts are available on the Black Jack Trailer Jack web site:  
[www.blackjacktrailerjacks.com.au](http://www.blackjacktrailerjacks.com.au)

For warranty replacement contact

Titan RV

Unit 5 Euro Business Park

26-34 Weippin Street Cleveland QLD 4163

P: +61 07 3286 1199 E: [info@blackjacktrailerjacks.com.au](mailto:info@blackjacktrailerjacks.com.au)

## 17. INTELLECTUAL PROPERTY

### Registered Trademark

Black Jack® Trailer Jacks is a registered trademark in Australia owned by Titan Stability Solutions Pty Ltd.

### Patent

The Black Jack Clamp is a registered patent in Australia (Patent NO 2021204066).

### Registered Design

The Black Jack Clamp is a registered design pending in Australia.

The Black Jack Master has a patent Pending in Australia (Patent NO 2025252517)

### Copyright

This "Black Jack® Maxi 2000kg 12V DC User Manual" is copyright protected and owned by Titan Stability Solutions Pty Ltd.

### Domain Name

[blackjacktrailerjacks.com.au](http://blackjacktrailerjacks.com.au) is a registered domain name owned by Titan Stability Solutions Pty Ltd.



## 18. COMPLIANCE

### 1. EMC Compliance

The Black Jack TM is EMC approved and compliant with:

EN 61000-6-3:2007+A1:2011+AC:2012

EN IEC 61000-6-1:2019

EN IEC 61000-3-2:2019

EN 6100-3-3:2013+A1:2019

### 2. Australian Standards for Gas Installations in Caravans

Gas Installations in Caravans AS\NZS 5601.2.2020 (Standard)

The Standard requires that an "ignition source" cannot be located within the clearances of an exchange gas cylinder.

The standard defines an "ignition source" as "A source of energy that can ignite an explosive atmosphere"

Note 1 to entry: Such sources include, but are not limited to flames, incandescent material, electrical sparks, hot surfaces, and mechanical impact sparks.

Note 2 to entry: For the purposes of domestic caravans and boats, items of equipment within a controlled area that are non sparking by nature or encapsulated are NOT considered to be ignition sources.

The Black Jack has been tested by an independent third party laboratory in Victoria and found to be compliant with the standard.

A Summary of the test report confirms:

**The tested electric powered Caravan and Trailer Jack model BJTJ series complied with the below tested clauses of the standard AS\NZS 5601.2.2020 +A1 2021.**

|                      |                                             |
|----------------------|---------------------------------------------|
| <b>Clause 1.3.41</b> | <b>Ignition Source Definition</b>           |
| <b>Clause 2.4.2</b>  | <b>Required Clearance</b>                   |
| <b>Clause 3.1.8</b>  | <b>Required Clearance around a cylinder</b> |
| <b>Clause 5.3</b>    | <b>Encapsulated devices</b>                 |

**The testing was carried out based on the information observed on the actual samples.**

For a copy of the report please contact us.

## ABOUT BLACK JACK®

Black Jack® Trailer Jacks is a division of Titan Stability Solutions Pty Ltd trading as Titan RV.



Our range of brands include:

### REDFOOT LEVELLING

Hydraulic auto levelling system for motorhomes, caravans, specialty vehicles and 5th wheelers.

[www.redfootlevelling.com.au](http://www.redfootlevelling.com.au)

### SWAYCONTROL HITCHES

The best selling Sway Control and Weight Distribution Hitches in the USA now available in Australia.

[www.swaycontrolhitches.com.au](http://www.swaycontrolhitches.com.au)

### BLACK JACK™ TRAILER JACK

Gone are the days of manually winding the jockey wheel to raise or lower the caravan or trailer.

[www.blackjacktrailerjacks.com.au](http://www.blackjacktrailerjacks.com.au)

# BLACK JACK®

## TRAILER JACK

### CONTACT US

Black Jack® Trailer Jacks is a division of Titan Stability Solutions Pty Ltd

**Titan RV**

Unit 5 Euro Business Park  
26-34 Weippin Street  
Cleveland QLD 4163  
AUSTRALIA

P: +61 07 3286 1199

E: [info@blackjacktrailerjacks.com.au](mailto:info@blackjacktrailerjacks.com.au)

V4  
August 2026

**[www.blackjacktrailerjacks.com.au](http://www.blackjacktrailerjacks.com.au)**